


총람

제품 장점



15EDGVM-THR-3.5-10030003471

Pluggable Terminal Blocksnominal current7A.Rated voltage(II /2):
250V,pitch:3.5mm,Color:black,Contact surface:Tin

제품 장점

- ☒ Suitable for SMT welding process
- ☒ The plug direction is perpendicular to PCB, Can meet the needs of different connectors

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	8A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.5mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~130℃
---------------------------------	-----------

약세사리

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터

발주 번호	10030003471
포장 단위	
MOQ	
제품 무게 (포장 제외)	