


## 총람

### 제품 장점



### DG65H-B-12020000779

Single layer PCB fence terminal,nominal current30A.Rated voltage(UL): 300V,Rated cross section:22~10AWG,pitch:1.1mm,Color:black,Contact surface:Tin

### 제품 장점

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Solder board installation, which can realize the electrical connection between the device and the PCB

### 제품 인증

## 기술 데이터

### 제품 도면

### 3D

□

### Connection capacity

AWG	20~10AWG
Torque	1.2N.m

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A
Rated current (D)	10A

### Item properties

Type of installation	PCB welding
----------------------	-------------

Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M4
Pitch	11mm
Number of potentials	5
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세사리

비즈니스 데이터

발주 번호	12020000779
포장 단위	135

MOQ	/
제품 무게 (포장 제외)	24.056