


총람

제품 장점



DGV10-10090000027

Through-wall terminal blocks, Rated current: 57A, Rated voltage (III/3) : 400V, width: 10.1mm, Color: gray, Contact surface :Tin

제품 장점

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~10mm ²
AWG	24~6AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	65A
Rated current (D)	10A
Rated current (C)	65A

Electrical parameters IEC

Rated current(III/3)	400V
Rated current	400V
	57A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세사리

tool

screwdriver	0.8x4.0mm, Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Marking strip	ZB10
Bridge	EB xx-10
Other	/

Accessories

Coding strip	/
Bridge	/
Marking strip	ZB10
Others	/

Tool

Operating tool	/
Screwdriver	1.0x4.0mm, Slotted screwdriver

비즈니스 데이터

발주 번호	10090000027
포장 단위	50
MOQ	

제품 무게 (포장 제외)	21.78
---------------	-------