

## 총람

### 제품 장점



## DG103-5.08-10040004776

PCB terminal blocks, Rated current: 24A, Rated voltage (Ⅲ/2) 250V, Cross section: 2.5mm<sup>2</sup>, pitch: 5.08mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

### 제품 장점

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

### 제품 인증



## 기술 데이터

### 제품 도면

### 3D

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~2.5mm<sup>2</sup>

Conductor cross section flexible

0.2~2.5mm<sup>2</sup>

AWG

24~12AWG

Torque

0.5N.m

Strip length

7mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated current(III/3)	250V
Rated current	24A
Rated current(III/2)	400V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세사리

tool

screwdriver	0.6x3.5mm,Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Marking strip	/
Bridge	/
Other	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

비즈니스 데이터	
발주 번호	10040004776
포장 단위	400
MOQ	
제품 무게 (포장 제외)	2.73