


총람

제품 장점



DG381S-HV-3.5-10040007488

PCB terminal blocks, Rated current: 10A, Rated voltage (Ⅲ/2) 200V, Cross section: 0.2-1.5mm², Pitch: 3.5mm, connectoon method: Screw connector with tension sleeve, Color: green, Contact surface :Tin

제품 장점

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ 45°connection can realize multi-row layout on PCB
- ☒ Fixed screw connection technology,safe and reliable
- ☒ Meet the UL D grade 300V

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Connection capacity

Conductor cross section solid	0.2~1.5mm ²
Conductor cross section flexible	0.2~1.5mm ²
AWG	26~16AWG
Torque	0.2N.m
Strip length	5mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	200V
Rated current(III/3)	160V
Rated current	10A
Rated current(III/2)	200V
Rated current(II/2)	400V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리	
tool	
screw driver	0.4x2.5mm, Slotted screwdriver

비즈니스 데이터	
발주 번호	10040007488
포장 단위	500
MOQ	
제품 무게 (포장 제외)	1.07