

총람

제품 장점



DG150-A-12010001050

Up and down transfer terminal, nominal current: 150A, Rated voltage: 1000A, Pitch: 27mm, Color: black, Contact surface: Ni

제품 장점

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ High current electrical connections at power end can be met

제품 인증



기술 데이터

제품 도면

3D

□

Wiring capacity

torque

5.6N.m

Connectable conductor cross section

6~1/0 AWG

Electrical parameters UL

Rated voltage

1000V

Rated current

150A

Item properties

Type of installation

panel

Pin arrangement

Single row in a straight line

Connection method

Screw connection

Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~120℃
---------------------------------	-----------

악세사리

비즈니스 데이터

발주 번호	12010001050
포장 단위	12
MOQ	12

제품 무게 (포장 제외)

2448