

## 총람

### 제품 장점



### DC4-HE-LD250-11020000121

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 250 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm<sup>2</sup> - 4mm<sup>2</sup>, AWG: 22 - 10, Width: 8 mm, Fuse type: Glass/ceramic/..., Fuse type: G / 5 x 20, Color: black, Suitable for 24 V DC LED, Mounting type: NS 35/7.5, NS 35/15.

### 제품 장점

- ☒ Fuse terminal blocks;
- ☒ Steel screw connection technology, reliable connection;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm <sup>2</sup>
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-2.5mm <sup>2</sup>
Conductor cross section flexible (ferrule without plastic sleeve)	0.5-4mm <sup>2</sup>
Strip length	8~9mm
Conductor cross section solid	0.5~6mm <sup>2</sup>

Conductor cross section flexible	0.5~4mm <sup>2</sup>
Conductor cross section solid AWG	22~10
screw thread	M3
Tightening torque	0.6N.m

#### Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

#### IEC Electrical parameters

Rated voltage (III / 3)	250V
Rated current (III / 3)	6.3A
Rated surge voltage	6KV

#### Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

#### Dimension

NS 35/7,5 Height	48mm
End plate width	1.5mm
NS 35/15 Height	55.5mm
length	58mm
width	8mm
Height	46.5mm

#### Overview

Connection method	screw connection
Number of rows	1
number of connections	2

Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

## 악세사리

### Marker

Top marker	/
Side marker	ZB8
Marker support	/

### Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	EBC2-8 / EBC3-8 / EBC10-8
End cover	D-DC4-HE
Partition plate	/

### Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

## 비즈니스 데이터

발주 번호	11020000121
포장 단위	50
MOQ	50

