


## 총람

### 제품 장점



### WS2.5T-DB-100A(H)-11030000199

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 28 - 14, Width: 10 mm, Color: gray, Mounting type: Panel installation

### 제품 장점

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Panel installation, no need to install on the guide rail.

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 8~9mm                  |
| Conductor cross section solid     | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~14                  |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 24A  |
| Rated surge voltage     | 8KV  |

Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

Dimension

|                 |       |
|-----------------|-------|
| End plate width | 2.5mm |
| length          | 28mm  |
| width           | 10mm  |
| Height          | 18mm  |

Overview

|                                           |                             |
|-------------------------------------------|-----------------------------|
| Connection type                           | Pull back spring connection |
| Number of rows                            | 1                           |
| number of connections                     | 4                           |
| Open-end side panels                      | Yes                         |
| Insulation Materials                      | PA                          |
| Flame retardant grade, in line with UL 94 | V0                          |

악세사리

Marker

|                |   |
|----------------|---|
| Top marker     | / |
| Side marker    | / |
| Marker support | / |
| Warning cover  | / |

Accessories

|                                                    |            |
|----------------------------------------------------|------------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5    |
| Adjacent jumper (2P)                               | /          |
| Alternate jumper (2P)                              | /          |
| Staggered jumper (2P)                              | /          |
| End cover                                          | D-WS2.5-DB |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| DIN rail mounting adapter     | WHH-WS1.5-DB                          |
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

비즈니스 데이터

|               |             |
|---------------|-------------|
| 발주 번호         | 11030000199 |
| 포장 단위         | 100         |
| MOQ           | 100         |
| 제품 무게 (포장 제외) | 4           |