

종람

#### 제품 장점



# FEAC-T-032A-P4-03-0.0M-22070000058

A charging socket for a charging post, cable-free, for charging electric vehicles (evs) using alternating current (AC) , Type 2, IEC 62196-2,32A/480V (AC), enclosure: Black, DEGSON logo

제품 장점

☑All Degson vehicle sockets and plug-in power supply sockets are designed in a unified manne

☑Both power and signal contacts are silver plated

☑passed IATF 16949:2016 certification

☑It conforms to human mechanics and is easy to operate

제품 인증





기술 데이터

제품 도면

3D

#### **Environmental conditions**

Maximum altitude	5000m(Above sea level )
Ambient temperature (operation)	— 30 °C ~ 50 °C
Ambient temperature (storage / transport)	− 40 °C ~ 80 °C
IP class	IP54(coupling)

#### Electrical characteristics

Maximum charge power	26KW
Phase	3
Power pin quantity	5

Pated current of high power contacts	50
Rated current of high-power contacts	32
Power contact rated voltage	480
Quantity of signal contacts	2
Signal contact rated current	2
Signal contact rated voltage	30
Signal transmission type	Pulse width adjustment

## Mechanical properties

Insertion/pullout cycle	10000
Insertion force	< 100N
Pull out force	< 100N

## Marking material

Shell color	black	
Actuation component color	Silver	
Cover color	black	
Customization basis	Provided according to customer requirements	
Shell material	Plastic	
Protective cover material	Plastic	
Flammability rating	VO	
Contact surface material	Ag	

## **Environmental Product Compliance**

REACH	conform
China RoHS	conform

## Dimension

Vahiala aannaatan haimht	45 mm/\/ahiala aharring aannaatar\
Vehicle connector height	45mm(Vehicle charging connector)

Vehicle connector width	100mm(Vehicle charging connector)
-------------------------	-----------------------------------

악세사리

비즈	드니스	: 데	이터
----	-----	-----	----

22070000058
36
0.474kg