

종람		
제품 장점		
	A charging socket for	A-P4-03-0.0M-22070000035 a charging post, cable-free, for charging electric alternating current (AC), Type 2, IEC 62196-2,16A/480V ck, DEGSON logo
제품 장점		
 All Degson vehicle sockets and plug-in power supply sockets are designed in a unified manne Both power and signal contacts are silver plated passed IATF 16949:2016 certification It conforms to human mechanics and is easy to operate 		
제품 인증		
△ (€	CB	
기술 데이터		
제품 도면		
3D		
Environmental conditions		
Maximum altitude		5000m(Above sea level)
Ambient temperature (operation)		— 30 °C ~ 50 °C
Ambient temperature (storage / transport)		— 40 °C ~ 80 °C
IP class		IP54(coupling)
Electrical characteristics		
Maximum charge power		13KW
Phase		3
Power pin quantity		5

Intervention ingrinome contacts 16 Power contact rated voltage 490 Quantity of signal contacts 2 Signal contact rated current 2 Signal contact rated voltage 30 Machanical properties Pulse width adjustment Mechanical properties 10000 Insertion force <100N Pull out force <100N Actuation component color Silver Cover color black Cover color black Shell material Provided according to customer requirements Shell material Plastic Protective cover material Plastic Flammability rating V0 Contact surface material Ag Environmental Product Compliance Conform China RoHS conform	Poted ourrent of high power contacts	50
Quantity of signal contacts 2 Signal contact rated current 2 Signal contact rated current 30 Signal contact rated voltage 30 Signal transmission type Pulse width adjustment Insertion/pullout cycle 10000 Insertion force <100N	Rated current of high-power contacts	16
Signal contact rated ourrent 2 Signal contact rated voltage 30 Signal transmission type Pulse width adjustment Kechanical properties 10000 Insertion/pullout cycle 10000 Insertion force <100N	Power contact rated voltage	480
Signal contact rated voltage 30 Signal transmission type Pulse width adjustment Mechanical properties 10000 Insertion/pullout cycle 10000 Insertion force <100N	Quantity of signal contacts	2
Signal transmission type Pulse width adjustment Mechanical properties 10000 Insertion/pullout cycle 10000 Insertion force <100N	Signal contact rated current	2
Mechanical properties Insertion/pullout cycle 10000 Insertion force <100N	Signal contact rated voltage	30
Insertion/pullout cycle 10000 Insertion force <100N	Signal transmission type	Pulse width adjustment
Insertion force <100N	Mechanical properties	
Pull out force < 10N	Insertion/pullout cycle	10000
Image: A cluade of a close of a clo	Insertion force	< 100N
Shell colorblackActuation component colorSilverCover colorblackCustomization basisProvided according to customer requirementsShell materialPlasticProtective cover materialPlasticFlarmability ratingV0Contact surface materialAgREACHREACHconformChina RoHSconform	Pull out force	< 100N
Actuation component colorSilverCover colorblackCustomization basisProvided according to customer requirementsShell materialPlasticProtective cover materialPlasticFlammability ratingV0Contact surface materialAgExerciseREACHconformChina RoHSconform	Marking material	
Cover colorblackCustomization basisProvided according to customer requirementsShell materialPlasticProtective cover materialPlasticFlammability ratingV0Contact surface materialAgREACHREACHconformChina RoHSconform	Shell color	black
Customization basisProvided according to customer requirementsShell materialPlasticProtective cover materialPlasticFlammability ratingV0Contact surface materialAgEnvironmental Product ComplianceREACHconformChina RoHSconform	Actuation component color	Silver
Shell material Plastic Protective cover material Plastic Flammability rating V0 Contact surface material Ag Environmental Product Compliance conform REACH conform China RoHS conform	Cover color	black
Protective cover material Plastic Flammability rating V0 Contact surface material Ag Environmental Product Compliance France REACH conform China RoHS conform	Customization basis	Provided according to customer requirements
Flammability rating V0 Contact surface material Ag Environmental Product Compliance conform REACH conform China RoHS conform	Shell material	Plastic
Contact surface material Ag Environmental Product Compliance conform REACH conform China RoHS conform	Protective cover material	Plastic
Environmental Product Compliance REACH China RoHS	Flammability rating	V0
REACH conform China RoHS conform	Contact surface material	Ag
China RoHS conform	Environmental Product Compliance	
	REACH	conform
Dimension	China RoHS	conform
	Dimension	
Vehicle connector height 45mm(Vehicle charging connector)	Vehicle connector height	45mm(Vehicle charging connector)

악세사리

비즈니스 데이터		
발주 번호	2207000035	
포장 단위	36	
MOQ		
제품 무계 (포장 제외)	0.474kg	