

종람

#### 제품 장점



# MAAC-S-080A-V-03-5.0M-22030000138

AC charging cable, with vehicle charging plug and free outlet, Type 1, SAE J1772:2017,80A/250V (AC), DEGSON logo, cable: 5M, Black

제품 장점

 $\ensuremath{\square}$  All of Degson's vehicle plugs and plug-in rechargeable piles are designed in a unified manner

☑ Both power and signal contacts are silver plated

☑ passed IATF 16949:2016 certification ☑ The handle is ergonomic and comes with an additional rubber handle assembly for ease of operation

제품 인증







기술 데이터

제품 도면

3D

### Cable

Cable composition	2*5AWG+1*6AWG+1*16AWG
Cable outer diameter	26.7±0.8mm

### **Environmental conditions**

Maximum altitude	5000m(Above sea level )
Ambient temperature (operation)	— 30 °C ~ 50 °C
Ambient temperature (storage / transport)	— 40 °C ~ 80 °C
IP class	IP67

#### Electrical characteristics

Maximum charge power	20KW
Phase	1
Power pin quantity	3
Power contact rated voltage	250
Quantity of signal contacts	2
Signal contact rated current	2
Signal contact rated voltage	30
Resistance coding	480Ω
Signal transmission type	Pulse width adjustment

## Mechanical properties

Insertion/pullout cycle	10000
Insertion force	< 75N
Pull out force	< 75N

### Marking material

Handle color	grey
Shell color	black
Actuation component color	Silver
Cover color	black
Customization basis	Provided according to customer requirements
Shell material	Plastic
Handle material area	Silicone Rubber
Protective cover material	Soft plastic
Flammability rating	VO
Contact surface material	Ag

## **Environmental Product Compliance**

REACH	conform
China RoHS	conform
Cable	
Wiring standard	UL62
Wiring level	5 class
Certification	UL
Wire type	Straight line
Outer sheath,color	black
Outer sheath, material	TPE
Electrical parameters	
Rated current	80A
Dimension	
Vehicle connector height	173.5mm(Vehicle charging connector)
Vehicle connector width	53.7mm(Vehicle charging connector)
Vehicle connector depth	244.3mm(Vehicle charging connector)
Strip length	100±10mm
Cable length	5000±100mm

악세사리	
Annex	
Empty seats	FAAC-V-03-01A(H)

비즈니스 데이터	
발주 번호	22030000138
포장 단위	5

MOQ	/
제품 무계 (포장 제외)	5.2KG