

종람			
제품 장점			
Ċ		Mobile AC charging box (ICCB/IC-CPD) f (AC) via European s	2A-VB-03-5.0M-00A(H)- 57 cable with vehicle charging connector and on-cable control for charging electric vehicles (EVs) with alternating current standard vehicle charging outlet, with protective cover, PVC e plug and IC-CPD, housing: Black, DEGSON electrical ck, straight head
제품 장점			
☑The power and ☑Has passed IAT	signal contacts are F 16949:2016 cert	e silver-plated tification	olugs adopt a unified design an additional rubber handle assembly for easy operation
제품 인증			
${\bf A}$	CE	CB	
기술 데이터			
제품 도면			
3D			
Environmental cor	nditions		
Maximum altitud	le		5000m(Above sea level )
Ambient temperature (operation)			— 30 °C ~ 50 °C
Ambient temperature (storage / transport)		ansport)	− 40 °C ~ 80 °C
IP class			IP54 (protection cover)

Electrical characteristics

Maximum charge power	7KW	
Phase	1	

Power pin quantity	3
Rated current of high-power contacts	32
Power contact rated voltage	250
Quantity of signal contacts	2
Signal contact rated current	2
Signal contact rated voltage	30
Resistance coding	220Ω
Signal transmission type	Pulse width adjustment
Mechanical properties	
Insertion/pullout cycle	10000
Insertion force	< 100N
Pull out force	< 100N
Marking material	
Actuation component color	Silver
Cover color	black
Customization basis	Provided according to customer requirements
Shell material	Plastic
Handle material area	Plastic
Protective cover material	Soft plastic
Flammability rating	V0
Contact surface material	Ag
Cable	
Cable composition	3*6mm <sup>2</sup> +1*0.75mm <sup>2</sup>
Wiring standard	EN50620

	CE
Certification	СВ
	τυν
Cable outer diameter	13±0.5mm
Wire type	Straight line
Cable resistance	≤ 0.0033 $\Omega$ /m (Based on the power core, at an ambient temperature of 20°C)
Outer sheath,color	black
Minimum bend radius	78mm
Outer sheath, material	PUR
laterial data	
Environmental items	Compliant with REACH/RoHS
Shell color	black
imension	
Vehicle connector height	79mm(Vehicle charging connector)
Vehicle connector depth	222.3mm(Vehicle charging connector)
Strip length	100±10mm
Cable length	5000±50mm
width	70mm

악세사리		
Annex		
Empty seats	FEAC-V-03-01A(H)	

비즈니스 데이터	
발주 번호	22020000457

포장 단위	5
MOQ	
제품 무계 (포장 제외)	2.85kg