

## 총람

### 제품 장점



### 5EDGKDL-7.62-10020003440

Pluggable Terminal Blocks, Rated current: 41A, Rated voltage (III/2) : 1000V, Cross section: 6mm<sup>2</sup>, Pitch: 7.62mm, Color: Green, Connection method: Push-in spring connection, Color: Green, Contact surface: Tin

### 제품 장점

- ☒ Push-in spring connection, excellent anti-vibration performance, tool-free.
- ☒ Dual-Lever Spring patented technology, easy and comfortable operation.
- ☒ Levers status is optional (open/close), suitable for multi-core cable.

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D



### Connection capacity

Conductor cross section solid	0.2~10mm <sup>2</sup>
	0.2~6mm <sup>2</sup>
Strip length	12mm

### Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (D)	5A

Electrical parameters IEC

Rated voltage	1000V
Rated current(III/3)	800V
Rated current	41A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection method	Push-in spring connection
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	IIIb
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터	
발주 번호	10020003440
포장 단위	200
MOQ	
제품 무게 (포장 제외)	14.875