

총람

제품 장점



DG636-HT-7.62-10040007699

PCB terminal blocks, Rated current: 32A, Rated voltage (III/2) : 630V, Cross section: 0.2-4mm², Pitch: 7.62mm, Connection method: Screw connector with tension sleeve, Color: Green, Contact surface: Tin

제품 장점

- ☒ Fixed screw connection technology, safe and reliable
- ☒ High torque specification of M3.5 screw, more stable torque used by customers
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Connection capacity

Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	26~10AWG
Torque	1.2N.m
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V
Rated current (B)	30A
Rated current (D)	10A
Rated current (C)	30A

Electrical parameters IEC

Rated voltage	630V
Rated current(III/3)	500V
Rated current	32A
Rated current(III/2)	630V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M3.5
Pitch	7.62mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

약세사리

비즈니스 데이터	
발주 번호	10040007699
포장 단위	20
MOQ	
제품 무게 (포장 제외)	172.121